

Brouwer 1570 Sod Harvester

SPECIFICATIONS

Width of cut	16" (406mm) 18" (457mm) 21" (533mm) 24" (610mm)
Length of cut	24" (610mm) to 100" (2540mm)
Thickness of Cut (With Hydraulic Control & Remote Switch)	Up to 2 1/8" (54mm)
Performance	1500 Rolls (1260 M) per hour
Controls	Joystick for all main functions
Cutter/Conveyor Drives	Hydraulic
Cutting Blades	One Piece or 3 pc Blade
Conveyor & Roll Up	Rubber belt in STD or low profile or Mintex
Pallet Sizes	48" x 48" (1219mm x 1219mm) Std.
Construction	High strength steel weldment
Weight (Harvester)	8130 lbs. (3688 kg) (Harvester weight may vary on spec)

ACCESSORIES

- Roof frame cover and lights
- Brush Kit, Common Parts, Float
- 16"/18" Rotary brush rubber fingers
- 24" Rotary brush rubber fingers (4133373 - Brush Kit & Common Parts Required)
- 16"/18" Rotary brush - bristle
- 24" Rotary brush - bristle (4133373 - Brush Kit & Common Parts Required)
- Sod panel ext. 48" pallet
- Sod panel ext. 54" pallet
- Fold-down pallet forks
- Adjustable piling wall
- 16" Coulter kit
- 18" Coulter kit
- 24" Coulter kit
- Counter kit for rolled sod (standard on slabbing machines)
- Tractor weight kit (8 weights & mtg. rod)
- Euro Decal Kit For European Units Only (John Deere only)
- Euro Decal Kit For European Units Only (CNH/New Holland only)

STANDARD MODEL

STANDARD TRACTOR	
TRACTOR MODEL	New Holland T4020 Diesel
HORSE POWER	64 (Gross) 50 PTO
TRANSMISSION	8 x 8 Mech. Shuttle Optional Power Shuttle
TRACTION	2 wheel drive (4wd option)
STEERING	Hydro Power
TIRES	Front. 10L - 15 Rear 19.5 x 24 R4
WEIGHT (Tractor)	5776lbs (2620 kg)

UPGRADES

Tractor

[New Holland T4020 Power Shuttle Transmission](#)

54" Pallet
4-wheel drive

[John Deere - 5065E Syncro Shift Transmission](#)

54" Pallet
4-wheel drive

Steering

Manual (standard)
Auto steer - 2WD (optional)
Auto steer - 4WD (optional)

Manual (standard)
Auto steer - 2WD (optional)
Auto steer - 4WD (optional)

Stack Method	16"/18" Cutting width - Mech rolling (standard)
	24" Cutting width - Mech rolling (standard)
	16"/18" Cutting width - Hyd rolling (optional)
	24" Cutting width - Hyd rolling (optional)
	16"/18" Cutting width - Slabbing (optional)
	16"/18" Cutting width - Folding (optional)
Conveyor	16" Cutting width - Mintex
	18" Cutting width - Mintex
	24" Cutting width - Mintex
	16" Cutting width - Rubber
	18" Cutting width - Rubber
	24" Cutting width - Rubber
Blade	16" Standard
	18" Standard
	24" Standard
	16" Combination
	18" Combination
	24" Combination
	16" Uni-Blade
	18" Uni-Blade
	24" Uni-Blade
Cut-Off	16" Cutting width - Standard
	18" Cutting width - Standard
	24" Cutting width - Standard
	16" Cutting width - Serrated
	18" Cutting width - Serrated
	24" Cutting width - Serrated
Transfer (rolling only)	16" Cutting width - Catcher Basket (standard)
	18" Cutting width - Catcher Basket (standard)
	24" Cutting width - Catcher Basket (standard)
	16" Cutting width - Cross Conveyor (optional)
	18" Cutting width - Cross Conveyor (optional)
	24" Cutting width - Cross Conveyor (optional)