

# Burro Forklifts

## SPEC SHEET

### *Capacity*

Everything about the Burro is intended to be simple, reliable and lightweight. It can handle an impressive 3000 pound load at a 24" load center and lift it 65 inches. It is intended for use on improved surfaces such as, graded lots, parking areas, or paved surfaces. The Burro is great for delivering palletized materials with a single axle truck to stores, warehouses or job sites with suitable terrain. If you need rough terrain delivery, take a look at the Donkey. Standard Model

- Burro: 3000 pound Lift Capacity @24" Load Center
- Burro Engine
- Standard: Honda GX395 (11 HP)

### *Engine / Drive Train*

Powered by Honda's superb GX390 engine, the Burro's rear wheel is hydraulically driven. The engine is equipped with electric start for easy operation. A spring applied, hydraulic released brake is built in to the drive motor for added safety.

### *Mast*

The Burro takes advantage of the simple and highly reliable, single stage mast. Lift height is 65" - plenty of lift to unload any truck or trailer. The fork carriage can be fitted with fixed or adjustable width forks or 24" siding reach forks.

#### Burro Mast

Standard: 3000 pound capacity at 24" load center, 65" lift height

#### Burro 24" Reach - Load Spacing

The Burro load spacing is set to 51" so it can easily handle standard size pallets.

Standard: 51" load spacing

## ***Tires***

Several tire options are available for the Burro, including foam filled, solid and pneumatic versions.

- Standard Drive (rear): Foam Filled 18.5x8-8
- Optional Drive (rear): Pneumatic 18.5x8-8
- Standard Outrigger (front): Solid Rubber 4.00x8
- Optional Outrigger (front): Pneumatic 18.5x8-8
- Optional Outrigger (front): Foam Filled 18.5x8-8